

Patented Valve Packing



FIRE SAFE

*Slade Braided Graphite Foil
API Fire Test Certified*

**API 589 First Edition
API 607 Fourth Edition**

Tested by Southwest Research Institute
Witnessed by 3 EXXON Engineers

Performed under American Petroleum Institute grant

Temperatures reached 1876°F/1030°C
Exceeded API requirements by 95%

No die-forming or end rings required

Valves containing flammable fluids may be at risk during a fire if packages are not fire safe and tend to shrink from heat...

No Live Loading Required.

**SLADE Patented Packings
rated FIRE SAFE**

SLADE Inc.

181 Crawford Rd., Statesville, NC 28625
Tel: 704-873-1366 Fax: 704-873-1399

www.slade-inc.com



EMISSION SAFE

*Slade Braided Graphite Foil
USA Emission Standards Exceeded*

Exxon Emission Report

Using PERF procedures & standards...Slade braided packing outperformed standard die-formed graphite ribbon rings by 74%.

Corpus Report

Performed by a major petroleum refining company...96% of the 325 test reported 0 ppm emissions for Slade braided packing using EPA Ref. Method 21 procedures.

Cambridge Report

Major US Refinery reports on 282 field installed tests of Slade braided packing: 99% were below the 500 ppm goal.

(56% were 0 ppm: 96% were below 65 ppm).

Call Slade to request a report.

Approved for sealing VOC by Exxon, Shell, Chevron, Dupont, Eastman Chemical & other companies.

**Slade 3300G for Containment
of FUGITIVE EMISSIONS**

Distributed by:

POLYFLON[®]
Handelsgesellschaft m. b. H.

OOS
Österreichischer
Österreichischer
Österreichischer

ENet
EUROPEAN
EUROPEAN
EUROPEAN

Ihr Ansprechpartner in Dichtungsfragen!

8020 Graz
Baumkircherstraße 3
Tel.: ++43/316/71.10.89
Fax: ++43/316/71.89.55

www.polyflon.at

2371 Hinterbrühl
Gadnerstraße 36B
Tel.: ++43/2236/26.718
Fax: ++43/2236/46.811

office@polyflon.at